


gripSTIK® 3/4" Bullnose

gripSTIK® 3/4" Bullnose creates a smooth, rounded look to drywall corners. This easy-to-install 90° corner support can be nailed, stapled or applied with spray adhesive. The specially knurled and perforated flanges allow excellent joint compound adhesion. No mud additives or priming are needed prior to painting. Phillips bead is dent resistant, won't rust and easy to cut with shears, knife or fine-tooth hacksaw.




Product Data and Ordering Information Material:

Extruded rigid vinyl; contains no asbestos
 Dimensions: 7/8" leg x 7/8" leg, 3/4" radius
 Part Number: BN3VYL

Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton
10'	35	50	350

All Phillips products are made in the U.S.A.



ASTM and Code Standards

Phillips gripSTIK® 3/4" Bullnose meets or exceeds:

- ASTM C 1047 Standard Specification for Accessories for Gypsum Wallboard
- ASTM D 1784 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Compounds and Chlorinated Poly (Vinyl Chloride) (CPVC) Compounds
- ASTM D 3678 Standard Specification for Rigid Poly (Vinyl Chloride) (PVC) Interior-Profile Extrusions

SDS and other technical information available at www.phillipsmfg.com

Patents

U.S. Patents 6,295,776 and 6,691,476

Leed Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

Storage

Avoid damage and store in a covered area away from direct sunlight.

