

## kwikSTIK® Paper-Faced Tape-On Metal Corner Bead P1 Super Wide (PSW)



kwikSTIK® Paper-Faced Tape-On Metal Corner Bead Super Wide features wider flanges for more complete coverage. The product is essentially the same as P1 Deluxe Super Wide except P1 Super Wide utilizes slightly lighter steel making it a more economical product. Used on 90° outside corners with any standard drywall thickness for straight, precise corners. The rigid steel-reinforced corner is covered with a unique, high strength paper providing maximum strength and protection while preventing cracking caused by the movement or shrinkage of framing members. Install by pressing firmly into joint compound and removing excess compound with a drywall knife or clean rag.




### Product Data and Ordering Information

Material: 0.010 min thickness, minimum G40

Part Number: PSW10EGB

Length	Pieces Per Carton	Cartons Per Pallet	Feet Per Carton
8'	50	56	400
10'	50	56	500



Drawing not to scale

All Phillips products are made in the U.S.A.

### ASTM and Code Standards

All Phillips kwikSTIK® Paper-Faced Tape-On Metal Corner Beads meets or exceeds the following ASTM standards except this product utilizes slightly lighter steel that does not meet ASTM standard C1047. However, this product meets all other applicable ASTM standard requirements:

- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard\*
- ASTM A653 Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process

SDS and other technical information available at [www.phillipsmfg.com](http://www.phillipsmfg.com).

### Patents

U.S. Patents 6,295,776; 6,539,680; 6,722,092 and 7,013,610

### LEED Credits for Recycled Content

MR2 – The steel and vinyl used in Phillips Manufacturing products is 100% recyclable.

MR4 – Phillips Manufacturing steel and vinyl products have a minimum of:

Total recycled content:	30%
Post-consumer recycled content:	25%
Pre-consumer recycled content:	5%

### Storage

Avoid bending or other damage and store in a dry place protected from moisture.

