PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us

600S125-33 (Standard Punch)


Product Description: 6” Stud STR 20GA (1 1/4” Leg, 33mil)


Coating: G60 (standard), G90 (special order)

Specification Section: 09.22.16 (Non-Structural Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	6 in.	Yield Strength, Fy	33 ksi
Flange Width	1.25 in.	Design Thickness	0.0346 in.
Lip Length	0.188 in.	Min. Steel Thickness	0.0329 in.

GROSS PROPERTIES		
Area (in²)	Total cross-sectional steel area	0.297
Weight (lb/ft)	Linear weight per foot	1.01
Ix (in⁴)	Moment of inertia about the x-axis	1.410
Sx (in³)	Section modulus about the x-axis	0.470
Rx (in)	Radius of gyration about the x-axis	2.180
Iy (in⁴)	Moment of inertia about the y-axis	0.042
Ry (in)	Radius of gyration about the y-axis	0.375
EFFECTIVE PROPERTIES		
Ix (in³)	Effective moment of inertia (x-axis)	1.366
Sx (in³)	Effective section modulus (x-axis)	0.355
Ma (in-k)	Allowable bending moment-effective section modulus	7.01
Mad (in-k)	Allowable bending moment-distortional bucking	5.73
Va_g (lb)	Allowable shear force in web	638
Va_{net} (lb)	Allowable strong axis sheer at punchout	638
TORSIONAL PROPERTIES		
J x 1000 (in⁴)	St. Venant torsional constant	0.118
Cw (in⁶)	Warping constant	0.300
Xo (in)	Distance from shear center to centroid	-0.608
m (in)	Distance from shear center to mid-plane of web	0.399
Ro (in)	Polar radius of gyration	2.294
Beta	Torsional Flexural Constant	0.930





Non-structural punchout first punchout is centered 12” from beginning of member; subsequent punchouts are 24” on center (o.c.). Center of last punchout is no less than 12” from end of member.

Codes & Standards:

- **Nonstructural Members**
  - AISI S220
  - ASTM C645
  - ASTM C754
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**