Ready-Track® Framing



Ready Products give installers the flexibility to build curved wall and ceiling framing right on the jobsite. Engineered for ease and endlessly versatile, this system supports even the most challenging drywall designs involving arcs and bends. Ready-Track framing is simple to bend into smooth curves and it holds its shape without fasteners for easy positioning and installation. With flexible framing sections, Ready-Track creates a cold-formed steel (CFS) framing system that can help you realize unique curved designs.

Key Features

- Ideal for curved walls, stairwells, soffits, clouds and complicated compound radiuses
- Handles almost any application when you need material curved along the flange
- Screw holes in the bottom web allow the top-track radius to be locked down for easy replication, once fitted over the bottom track
- Optional screw holes in the leg allow the radius to be easily locked down from the side

Material

- 20 gauge (30 mil) and 18 gauge (43 mil)

Finish

- Zinc Galvanized, G60

Disclaimer

Some specific models of this product might not be covered in the associated code reports. Please verify coverage for the models you wish to use

Product Information Table

Model No.	Ga.	Thickness (mil)	Width (in.)	Length (in.)	Finish	Packaging Qty.
RT250-10	20	30	2 1/2	120	Zinc Galvanized, G60	10
RT250-8	20	30	2 1/2	96	Zinc Galvanized, G60	12
RT350-8	20	30	3 1/2	96	Zinc Galvanized, G60	12
RT362-10	20	30	3 5/8	120	Zinc Galvanized, G60	10
RT362-10-18	18	43	3 5/8	120	Zinc Galvanized, G60	10
RT362-8	20	30	3 5/8	96	Zinc Galvanized, G60	12
RT400-10	20	30	4	120	Zinc Galvanized, G60	10
RT400-8	20	30	4	96	Zinc Galvanized, G60	6
RT550-8	20	30	5 1/2	96	Zinc Galvanized, G60	6
RT600-10	20	30	6	120	Zinc Galvanized, G60	10
RT600-10-18	18	43	6	120	Zinc Galvanized, G60	6
RT600-8	20	30	6	96	Zinc Galvanized, G60	6
RT600-8-18	18	43	6	96	Zinc Galvanized, G60	6

1. Product is shipped in bundled, straight sections.