PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us

350S200-97 (Standard Punch)


Product Description: 3-1/2" Stud 12GA (2" Flange, 97 mil)


Coating: G60 (standard), G90 (Available)


Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	3.5 in.	Yield Strength, Fy	50 ksi
Flange Width	2 in.	Design Thickness	0.1017 in.
Lip Length	0.625 in.	Min. Steel Thickness	0.0966 in.

GROSS PROPERTIES		
Area (in^2)	Total cross-sectional steel area	0.813
Weight (lb/ft)	Linear weight per foot	2.77
Ix (in^4)	Moment of inertia about the x-axis	1.577
Sx (in^3)	Section modulus about the x-axis	0.901
Rx (in)	Radius of gyration about the x-axis	1.393
Iy (in^4)	Moment of inertia about the y-axis	0.440
Ry (in)	Radius of gyration about the y-axis	0.736
EFFECTIVE PROPERTIES		
Ix (in^3)	Effective moment of inertia (x-axis)	1.578
Sx (in^3)	Effective section modulus (x-axis)	0.886
Ma (in-k)	Allowable bending moment-effective section modulus	30.55
Mad (in-k)	Allowable bending moment-distortional bucking	30.55
Va_g (lb)	Allowable shear force in web	5705
Va_{net} (lb)	Allowable strong axis sheer at punchout	775
TORSIONAL PROPERTIES		
J x 1000 (in^4)	St. Venant torsional constant	2.803
Cw (in^6)	Warping constant	1.347
Xo (in)	Distance from shear center to centroid	-1.676
m (in)	Distance from shear center to mid-plane of web	0.994
Ro (in)	Polar radius of gyration	2.300
Beta	Torsional Flexural Constant	0.469







First punchout is centered 12" from beginning of member; subsequent punchouts are 24" on center (o.c.). Center of last punchout is no less than 12" from end of member.

Codes & Standards:

- **Structural Members**
  - ASTM C955
  - AISI S240
  - Installed per ASTM C1007
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**