PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us

362S250-68 (Standard Punch)


Product Description: 3-5/8" Stud 14GA (2-1/2" Flange, 68 mil)


Coating: G60 (standard), G90 (Available)


Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	3.625 in.	Yield Strength, Fy	50 ksi
Flange Width	2.5 in.	Design Thickness	0.0713 in.
Lip Length	0.625 in.	Min. Steel Thickness	0.0677 in.

GROSS PROPERTIES		
Area (in^2)	Total cross-sectional steel area	0.666
Weight (lb/ft)	Linear weight per foot	2.27
Ix (in^4)	Moment of inertia about the x-axis	1.491
Sx (in^3)	Section modulus about the x-axis	0.823
Rx (in)	Radius of gyration about the x-axis	1.496
Iy (in^4)	Moment of inertia about the y-axis	0.578
Ry (in)	Radius of gyration about the y-axis	0.931
EFFECTIVE PROPERTIES		
Ix (in^3)	Effective moment of inertia (x-axis)	1.491
Sx (in^3)	Effective section modulus (x-axis)	0.700
Ma (in-k)	Allowable bending moment-effective section modulus	20.94
Mad (in-k)	Allowable bending moment-distortional bucking	22.30
Va_g (lb)	Allowable shear force in web	4370
Va_{net} (lb)	Allowable strong axis sheer at punchout	1004
TORSIONAL PROPERTIES		
J x 1000 (in^4)	St. Venant torsional constant	1.129
Cw (in^6)	Warping constant	1.837
Xo (in)	Distance from shear center to centroid	-2.165
m (in)	Distance from shear center to mid-plane of web	1.259
Ro (in)	Polar radius of gyration	2.791
Beta	Torsional Flexural Constant	0.398







First punchout is centered 12" from beginning of member; subsequent punchouts are 24" on center (o.c.). Center of last punchout is no less than 12" from end of member.

Codes & Standards:

- **Structural Members**
  - ASTM C955
  - AISI S240
  - Installed per ASTM C1007
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**