PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us

400S137-33 (Standard Punch)


Product Description: 4” Stud STR 20GA (1-3/8” Flange, 33 mil)


Coating: G60 (standard), G90 (Available)


Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	4 in.	Yield Strength, Fy	33 ksi
Flange Width	1.375 in.	Design Thickness	0.0346 in.
Lip Length	0.375 in.	Min. Steel Thickness	0.0329 in.

GROSS PROPERTIES		
Area (in^2)	Total cross-sectional steel area	0.249
Weight (lb/ft)	Linear weight per foot	0.85
Ix (in^4)	Moment of inertia about the x-axis	0.603
Sx (in^3)	Section modulus about the x-axis	0.302
Rx (in)	Radius of gyration about the x-axis	1.556
Iy (in^4)	Moment of inertia about the y-axis	0.061
Ry (in)	Radius of gyration about the y-axis	0.496
EFFECTIVE PROPERTIES		
Ix (in^3)	Effective moment of inertia (x-axis)	0.603
Sx (in^3)	Effective section modulus (x-axis)	0.269
Ma (in-k)	Allowable bending moment-effective section modulus	5.31
Mad (in-k)	Allowable bending moment-distortional bucking	4.98
Va_g (lb)	Allowable shear force in web	976
Va_{net} (lb)	Allowable strong axis sheer at punchout	595
TORSIONAL PROPERTIES		
J x 1000 (in^4)	St. Venant torsional constant	0.099
Cw (in^6)	Warping constant	0.204
Xo (in)	Distance from shear center to centroid	-0.965
m (in)	Distance from shear center to mid-plane of web	0.597
Ro (in)	Polar radius of gyration	1.897
Beta	Torsional Flexural Constant	0.741







First punchout is centered 12” from beginning of member; subsequent punchouts are 24” on center (o.c.). Center of last punchout is no less than 12” from end of member.

Codes & Standards:

- **Structural Members**
  - ASTM C955
  - AISI S240
  - Installed per ASTM C1007
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**