PRODUCT SUBMITTAL SHEET


For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us


1200S162-118 (Standard Punch)


Product Description: 12” Stud 10GA (1-5/8” Flange, 118 mil)
Coating: G60 (standard), G90 (Available)
Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	12 in.	Yield Strength, Fy	50 ksi
Flange Width	1.625 in.	Design Thickness	0.1242 in.
Lip Length	0.500 in.	Min. Steel Thickness	0.1180 in.

GROSS PROPERTIES		
Area (in^2)	Total cross-sectional steel area	1.904
Weight (lb/ft)	Linear weight per foot	6.48
Ix (in^4)	Moment of inertia about the x-axis	32.158
Sx (in^3)	Section modulus about the x-axis	5.360
Rx (in)	Radius of gyration about the x-axis	4.110
Iy (in^4)	Moment of inertia about the y-axis	0.377
Ry (in)	Radius of gyration about the y-axis	0.445
EFFECTIVE PROPERTIES		
Ix (in^3)	Effective moment of inertia (x-axis)	32.154
Sx (in^3)	Effective section modulus (x-axis)	5.151
Ma (in-k)	Allowable bending moment-effective section modulus	154.22
Mad (in-k)	Allowable bending moment-distortional bucking	138.87
Va_g (lb)	Allowable shear force in web	14982
Va_{net} (lb)	Allowable strong axis sheer at punchout	11034
TORSIONAL PROPERTIES		
J x 1000 (in^4)	St. Venant torsional constant	9.788
Cw (in^6)	Warping constant	12.002
Xo (in)	Distance from shear center to centroid	-0.670
m (in)	Distance from shear center to mid-plane of web	0.459
Ro (in)	Polar radius of gyration	4.188
Beta	Torsional Flexural Constant	0.974







First punchout is centered 12” from beginning of member; subsequent punchouts are 24” on center (o.c.). Center of last punchout is no less than 12” from end of member.

Codes & Standards:

- **Structural Members**
  - ASTM C955
  - AISI S240
  - Installed per ASTM C1007
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**