PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us

1200S350-54[1] (Standard Punch)

Product Description: 12” Stud 16GA (3-1/2” Flange, 54 mil)


Coating: G60 (standard), G90 (Available)


Specification Section: 05.40.00 (Cold-Formed Metal Framing)


GEOMETRIC PROPERTIES			
Web Depth	12 in.	Yield Strength, Fy	50 ksi
Flange Width	3.500 in.	Design Thickness	0.0566 in.
Lip Length	1.000 in.	Min. Steel Thickness	0.0538 in.

GROSS PROPERTIES		
Area (in²)	Total cross-sectional steel area	1.165
Weight (lb/ft)	Linear weight per foot	3.96
Ix (in⁴)	Moment of inertia about the x-axis	24.866
Sx (in³)	Section modulus about the x-axis	4.144
Rx (in)	Radius of gyration about the x-axis	4.620
Iy (in⁴)	Moment of inertia about the y-axis	1.866
Ry (in)	Radius of gyration about the y-axis	1.266
EFFECTIVE PROPERTIES		
Ix (in³)	Effective moment of inertia (x-axis)	24.159
Sx (in³)	Effective section modulus (x-axis)	2.707
Ma (in-k)	Allowable bending moment-effective section modulus	67.67
Mad (in-k)	Allowable bending moment-distortional bucking	31.32
Va_g (lb)	Allowable shear force in web	1377
Va_{net} (lb)	Allowable strong axis sheer at punchout	1102
TORSIONAL PROPERTIES		
J x 1000 (in⁴)	St. Venant torsional constant	1.244
Cw (in⁶)	Warping constant	54.279
Xo (in)	Distance from shear center to centroid	-2.363
m (in)	Distance from shear center to mid-plane of web	1.478
Ro (in)	Polar radius of gyration	5.342
Beta	Torsional Flexural Constant	0.804

**1 Web-height to thickness ratio exceeds 200. Web Stiffeners are required at all support points and concentrated loads.*







First punchout is centered 12” from beginning of member; subsequent punchouts are 24” on center (o.c.). Center of last punchout is no less than 12” from end of member.

Codes & Standards:

- **Structural Members**
  - ASTM C955
  - AISI S240
  - Installed per ASTM C1007
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**