PRODUCT SUBMITTAL SHEET

For more information or questions, please contact:
Super Stud: technical@buysuperstud.com
EB Metal US: technical@ebmetal.us

600T150-68 Track

Product Description: 6” Track 14GA (1-1/2” Leg, 68mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 05.40.00 (Cold-Formed Metal Framing)





GEOMETRIC PROPERTIES			
Web Depth	6 in.	Yield Strength, Fy	50 ksi
Leg Width	1.500 in.	Design Thickness	0.0713 in.
		Min. Steel Thickness	0.0677 in.

GROSS PROPERTIES		
Area (in2)	Total cross-sectional steel area	0.641
Weight (lb/ft)	Linear weight per foot	2.18
Ix (in^4)	Moment of inertia about the x-axis	3.310
Sx (in^3)	Section modulus about the x-axis	1.059
Rx (in)	Radius of gyration about the x-axis	2.273
Iy (in^4)	Moment of inertia about the y-axis	0.113
Ry (in)	Radius of gyration about the y-axis	0.419
EFFECTIVE PROPERTIES		
Ix (in^3)	Effective moment of inertia (x-axis)	3.165
Sx (in^3)	Effective section modulus (x-axis)	0.893
Ma (in-k)	Allowable bending moment-effective section modulus	26.72
Va_g (lb)	Allowable shear force in web	5352
TORSIONAL PROPERTIES		
J x 1000 (in^4)	St. Venant torsional constant	1.0855
Cw (in^6)	Warping constant	0.797
Xo (in)	Distance from shear center to centroid	-0.669
m (in)	Distance from shear center to mid-plane of web	0.430
Ro (in)	Polar radius of gyration	2.406
Beta	Torsional Flexural Constant	0.923

Codes & Standards:

- **Structural Members**
  - ASTM C955
  - AISI S240
  - Installed per ASTM C1007
- **Material Standards**
  - ASTM A1003/A1003M
  - ASTM A653/A653M
- **Design Standards**
  - AISI S100-16 (2020) w/S2-20
- **Building Codes**
  - International Building Code (IBC) 2006–2024

- **Sustainability & Compliance:**
  - SFIA Quality Certified Manufacturing
  - Industry-Wide EPD Participant
  - HPD Documentation Available Upon Request
  - LEED Documentation Available Upon Request
  - Buy America / Build America (BABA) Documentation Available Upon Request
  - Manufactured in USA

NEW HAMPSHIRE | NEW JERSEY | MISSISSIPPI
Stronger **Together.**