

Product Category: Structural Metal Stud Framing: Specification Section 05 40 00

Available Coatings: G60 (standard); or G90

Yield Strength: 50 ksi

Product Name: 11-1/2TR14

AISI Nomenclature: 1150T125-68

Product Description: 11-1/2 inch 14 gauge track member with 1-1/4 inch flanges

Material and Shape Property Notes:

Thickness: Design: 0.0713" • Minimum: 0.0677" • Designation: 68 mil • Equivalent Gauge: 14
Flange width: 1-1/4" • Web Depth: 11-1/2"

SECTION PROPERTIES

Gross Section Properties:


Cross Section Area (**A**): 0.993 in²
Member Weight: 3.378 pounds per foot
Moment of Inertia, strong axis (**I_x**): 14.864 in⁴
Radius of Gyration, strong axis (**R_x**): 3.870 in.
Moment of Inertia, weak axis (**I_y**): 0.074 in⁴
Radius of Gyration, weak axis (**R_y**): 0.273 in.

Effective Section Properties:^[1]

Effective Section Modulus (**S_{x eff}**): 2.530 in³
Allowable Bending Moment (**M_a**): 62.747 inch-kips
Gross Allowable Shear (**V_a**): 2.671 kips

Torsional Properties:



St. Venant Torsional Constant (**J** x 1000): 1.682 in⁴
Warping Constant (**C_w**): 2.041 in⁶
Polar Radius of Gyration (**R_o**): 3.895 in
Distance from shear center (**X_o**): -0.345 in
Beta (**β**): 0.992 Flat web to thickness ratio (**h/t**): 158.920



CODES & STANDARDS

Super Stud products comply with the applicable provisions of the following:

International Building Code (IBC) 2006 - 2015
Sheet Steel: ASTM A1003 & ASTM A653
Galvanized Coating: ASTM A653
Members & Tolerances: ASTM C955
Meets ASTM C1007 when installed properly in structure
3rd Party Certification: Manufacturing verified & inspected
by Home Innovation Research Labs, Inc.



[1] Where "NC" appears, the effective properties have not been calculated, due to limits in the American Iron and Steel Institute (AISI) North American Specification for the Design of Cold-Formed Steel Structural Members (AISI S100).

The Super Stud Building Products Family of Companies