

Product Category: Structural Metal Stud Framing: Specification Section 05 40 00
Available Coatings: G60 (standard); or G90 **Yield Strength:** 50 ksi
Product Name: 3-5/8TR10 **AISI Nomenclature:** 362T125-118
Product Description: 3-5/8 inch 10 gauge track member with 1-1/4 inch flanges

Material and Shape Property Notes:

Thickness: Design: 0.1242" • Minimum: 0.1180" • Designation: 118 mil • Equivalent Gauge: 10
Flange width: 1-1/4" • Web Depth: 3-5/8"

SECTION PROPERTIES

Gross Section Properties:


Cross Section Area (**A**): 0.7574 in²
Member Weight: 2.5752 pounds per foot
Moment of Inertia, strong axis (**I_x**): 1.669 in⁴
Radius of Gyration, strong axis (**R_x**): 1.4842 in.
Moment of Inertia, weak axis (**I_y**): 0.0985 in⁴
Radius of Gyration, weak axis (**R_y**): 0.3607 in.

Effective Section Properties:^[1]

Effective Section Modulus (**S_{x eff}**): 0.8220 in³
Allowable Bending Moment (**M_a**): 28.28 inch-kips
Gross Allowable Shear (**V_a**): 8.009 kips

Torsional Properties:


St. Venant Torsional Constant (**J x 1000**): 3.895 in⁴
Warping Constant (**C_w**): 0.252 in⁶
Polar Radius of Gyration (**R_o**): 1.653 in
Distance from shear center (**X_o**): -0.633 in
Beta (**β**): 0.8534



CODES & STANDARDS

Super Stud products comply with the applicable provisions of the following:

International Building Code (IBC) 2006 - 2015
Sheet Steel: ASTM A1003 & ASTM A653
Galvanized Coating: ASTM A653
Members & Tolerances: ASTM C955
Meets ASTM C1007 when installed properly in structure
3rd Party Certification: Manufacturing verified & inspected
by Home Innovation Research Labs, Inc.



[1] Where "NC" appears, the effective properties have not been calculated, due to limits in the American Iron and Steel Institute (AISI) North American Specification for the Design of Cold-Formed Steel Structural Members (AISI S100).

The Super Stud Building Products Family of Companies