

Product Category: Structural Metal Stud Framing: Specification Section 05 40 00

Available Coatings: G60 (standard); or G90

Yield Strength: 50 ksi

Product Name: 8TW14

AISI Nomenclature: 800T200-68

Product Description: 8 inch 14 gauge track member with 2 inch flanges

Material and Shape Property Notes:

Thickness: Design: 0.0713" • Minimum: 0.0677" • Designation: 68 mil • Equivalent Gauge: 14
Flange width: 2" • Web Depth: 8"

SECTION PROPERTIES

Gross Section Properties:

Cross Section Area (**A**): 0.8545 in²

Member Weight: 2.9053 pounds per foot

Moment of Inertia, strong axis (**I_x**): 7.7869 in⁴

Radius of Gyration, strong axis (**R_x**): 3.0188 in.

Moment of Inertia, weak axis (**I_y**): 0.2719 in⁴

Radius of Gyration, weak axis (**R_y**): 0.5641 in.

Effective Section Properties:^[1]

Effective Section Modulus (**S_{x eff}**): 1.3119 in³

Allowable Bending Moment (**M_a**): 39.2780 inch-kips

Gross Allowable Shear (**V_a**): 4.0860 kips

Torsional Properties:


St. Venant Torsional Constant (**J** x 1000): 1.4480 in⁴

Warping Constant (**C_w**): 3.2947 in⁶

Polar Radius of Gyration (**R_o**): 3.2036 in

Distance from shear center (**X_o**): -0.9121 in

Beta (**β**): 0.9189



CODES & STANDARDS

Super Stud products comply with the applicable provisions of the following:

International Building Code (IBC) 2006 - 2015


Sheet Steel: ASTM A1003 & ASTM A653

Galvanized Coating: ASTM A653

Members & Tolerances: ASTM C955

Meets ASTM C1007 when installed properly in structure

3rd Party Certification: Manufacturing verified & inspected
by Home Innovation Research Labs, Inc.



[1] Where "NC" appears, the effective properties have not been calculated, due to limits in the American Iron and Steel Institute (AISI) North American Specification for the Design of Cold-Formed Steel Structural Members (AISI S100).

The Super Stud Building Products Family of Companies

