

## 362S250-68 (Standard Punch)



Product Description: 3-5/8" Stud 14GA (2-1/2" Flange, 68 mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	3.625 in.	Yield Strength, Fy	50 ksi
Flange Width	2.5 in.	Design Thickness	0.0713 in.
Lip Length	0.625 in.	Min. Design Thickness	0.0677 in.

GROSS PROPERTIES		
Area (in <sup>2</sup> )	Total cross-sectional steel area	0.666
Weight (lb/ft)	Linear weight per foot	2.27
I <sub>x</sub> (in <sup>4</sup> )	Moment of inertia about the x-axis	1.491
S <sub>x</sub> (in <sup>3</sup> )	Section modulus about the x-axis	0.823
R <sub>x</sub> (in)	Radius of gyration about the x-axis	1.496
I <sub>y</sub> (in <sup>4</sup> )	Moment of inertia about the y-axis	0.578
R <sub>y</sub> (in)	Radius of gyration about the y-axis	0.931
EFFECTIVE PROPERTIES		
I <sub>x</sub> (in <sup>3</sup> )	Effective moment of inertia (x-axis)	1.491
S <sub>x</sub> (in <sup>3</sup> )	Effective section modulus (x-axis)	0.700
M <sub>a</sub> (in-k)	Allowable bending moment-effective section modulus	20.94
M <sub>ad</sub> (in-k)	Allowable bending moment-distortional buckling	22.30
V <sub>g</sub> (lb)	Allowable shear force in web	4370
V <sub>net</sub> (lb)	Allowable strong axis shear at punchout	1004
TORSIONAL PROPERTIES		
J x 1000 (in <sup>4</sup> )	St. Venant torsional constant	1.129
C <sub>w</sub> (in <sup>6</sup> )	Warping constant	1.837
X <sub>o</sub> (in)	Distance from shear center to centroid	-2.165
m (in)	Distance from shear center to mid-plane of web	1.259
R <sub>o</sub> (in)	Polar radius of gyration	2.791
Beta	Torsional Flexural Constant	0.398



First punchout is centered 12" from beginning of member; subsequent punchouts are 24" on center (o.c.). Center of last punchout is no less than 12" from end of member.

### CODES AND STANDARDS:

Super Stud products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20 (effective properties include cold-work strength increase)
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M

### Structural Members:

- ASTM C955; AISI S240
- Installed per ASTM C1007

### Additional Standards:

- AISI S201; AISI S202

### 3rd Party Certification

For LEED Letter requests please submit through: [www.buysuperstud.com](http://www.buysuperstud.com)