



Super Stud Building Products - Product Submittal

Technical Services: technical@buysuperstud.com

800-477-7883
buysuperstud.com

New Jersey
2960 Woodbridge Avenue
Edison, NJ 08837
732-662-6200

Mississippi
53 W L Runnels Industrial Dr
Hattiesburg, MS 39401
601-584-7550

Specification Section: 09.22.16 (Non-Structural Metal Framing)

362T200-33 (33ksi) Track

33mil (STR 20 ga) Coating: G60 (standard), G90 (special order)

Geometric Properties

Web Depth	3.625 in	Yield Strength, F_y	33 ksi
Flange Width	2 in	Ultimate, F_u	45 ksi
Design Thickness	0.0346 in	Min. Steel Thickness	0.0329 in

Gross Section Properties

Cross Sectional Area (A)	0.2637 in ²
Product Weight per Linear Foot	0.8966 lb/ft
Moment of Inertia (I_x)	0.6193 in ⁴
Section Modulus (S_x)	0.3285 in ³
Radius of Gyration (r_x)	1.5325 in
Weak Axis Moment of Inertia (I_y)	0.1096 in ⁴
Weak Axis Radius of Gyration (r_y)	0.6447 in
Depth-to-Thickness Ratio (h/t)	98

Effective Section Properties, Strong Axis

Effective Area (A_e)	0.1112 in ²
Moment of Inertia for Deflection (I_{xe})	0.4317 in ⁴
Section Modulus (S_{xe})	0.1905 in ³
Allowable Bending Moment (M_a)	3.7648 in-k
Allowable Shear Force in Web (at Punchout) (V_y)	1,024 lb

Torsional Properties

St. Venant Torsion Constant ($J \times 1000$)	0.1052 in ⁴
Warping Constant (C_w)	0.2629 in ⁶
Distance from Shear Center to Neutral Axis (X_o)	1.2811 in
Radius of Gyration (r_o)	2.0989 in
Torsional Flexural Constant (Beta)	0.6275

Codes and Standards

Super Stud products comply with the applicable provisions of the following:

International Building Code (IBC): 2006 – 2024

Complies with AISI S100-16 (2020) w/S2-20. Effective properties incorporate the strength increase from the cold work of forming

Sheet steel: ASTM A1003/A1003M; ASTM A653/A653M

Galvanized coating: ASTM A653/A653M

Nonstructural:

Members and tolerances: ASTM C645; AISI S220, AISI S201, AISI S202

Meets ASTM C754 when installed properly in structure.


Structural:

Members and tolerances: ASTM C955; AISI S240, AISI S201, AISI S202

Meets ASTM C1007 when installed properly in structure.

Tested for fire resistance in accordance with ASTM E119 and UL 263.

3rd party Certification



Sustainability

For LEED letters contact Technical Services at technical@buysuperstud.com or visit

© 2025 Super Stud Building Products