

162S125-33 (Standard Punch)



Product Description: 1-5/8" Stud STR 20GA (1-1/4" Flange, 33mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 09.22.16 (Non-Structural Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	1.625 in.	Yield Strength, Fy	33 ksi
Flange Width	1.25 in.	Design Thickness	0.0346 in.
Lip Length	0.188 in.	Min. Steel Thickness	0.0329 in.

GROSS PROPERTIES		
Area (in ²)	Total cross-sectional steel area	0.145
Weight (lb/ft)	Linear weight per foot	0.49
I _x (in ⁴)	Moment of inertia about the x-axis	0.067
S _x (in ³)	Section modulus about the x-axis	0.083
R _x (in)	Radius of gyration about the x-axis	0.679
I _y (in ⁴)	Moment of inertia about the y-axis	0.028
R _y (in)	Radius of gyration about the y-axis	0.440
EFFECTIVE PROPERTIES		
I _x (in ³)	Effective moment of inertia (x-axis)	0.066
S _x (in ³)	Effective section modulus (x-axis)	0.070
M _a (in-k)	Allowable bending moment-effective section modulus	1.38
M _{ad} (in-k)	Allowable bending moment-distortional buckling	1.28
V _a (lb)	Allowable shear force in web	601
V _a _{net} (lb)	Allowable strong axis sheer at punchout	105
TORSIONAL PROPERTIES		
J x 1000 (in ⁴)	St. Venant torsional constant	0.058
C _w (in ⁶)	Warping constant	0.016
X _o (in)	Distance from shear center to centroid	-1.010
m (in)	Distance from shear center to mid-plane of web	0.583
R _o (in)	Polar radius of gyration	1.294
Beta	Torsional Flexural Constant	0.391



Non-structural punchout first punchout is centered 12" from beginning of member; subsequent punchouts are 24" on center (o.c.). Center of last punchout is no less than 12" from end of member.

CODES AND STANDARDS:

Super Stud/EB Metal US products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M

Structural Members:

- ASTM C955; AISI S240
- Installed per ASTM C1007

Additional Standards:

- AISI S201; AISI S202
- 3rd Party Certification

For LEED Letter requests please submit through:
www.buysuperstud.com or www.ebmetal.us

NEW HAMPSHIRE FACILITY
 12 TALLWOOD DRIVE
 BOW, NH 03304
 P: 603-216-1573

MISSISSIPPI FACILITY
 53 W L RUNNELS IND DR
 HATTIESBURG, MS 39401
 P: 601-584-7550

NEW JERSEY FACILITY
 2960 WOODBRIDGE AVE
 EDISON, NJ 08837
 P: 732-662-6200