

600S300-43 (Standard Punch)



Product Description: 6" Stud 18GA (3" Flange, 43 mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	6 in.	Yield Strength, Fy	33 ksi
Flange Width	3 in.	Design Thickness	0.0451 in.
Lip Length	0.625 in.	Min. Steel Thickness	0.0428 in.

GROSS PROPERTIES		
Area (in ²)	Total cross-sectional steel area	0.582
Weight (lb/ft)	Linear weight per foot	1.979
I _x (in ⁴)	Moment of inertia about the x-axis	3.483
S _x (in ³)	Section modulus about the x-axis	1.161
R _x (in)	Radius of gyration about the x-axis	2.446
I _y (in ⁴)	Moment of inertia about the y-axis	0.711
R _y (in)	Radius of gyration about the y-axis	1.105
EFFECTIVE PROPERTIES		
I _x (in ³)	Effective moment of inertia (x-axis)	3.053
S _x (in ³)	Effective section modulus (x-axis)	0.931
M _a (in-k)	Allowable bending moment-effective section modulus	15.361
M _{ad} (in-k)	Allowable bending moment-distortional buckling	16.336
V _g (lb)	Allowable shear force in web	1415
V _{net} (lb)	Allowable strong axis shear at punchout	1240
TORSIONAL PROPERTIES		
J x 1000 (in ⁴)	St. Venant torsional constant	0.395
C _w (in ⁶)	Warping constant	5.089
X _o (in)	Distance from shear center to centroid	2.311
m (in)	Distance from shear center to mid-plane of web	1.377
R _o (in)	Polar radius of gyration	3.542
Beta	Torsional Flexural Constant	0.574



First punchout is centered 12" from beginning of member; subsequent punchouts are 24" on center (o.c.). Center of last punchout is no less than 12" from end of member.

CODES AND STANDARDS:

Super Stud/EB Metal US products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M

Structural Members:

- ASTM C955; AISI S240
- Installed per ASTM C1007

Additional Standards:

- AISI S201; AISI S202

3rd Party Certification

For LEED Letter requests please submit through:
www.buysuperstud.com or www.ebmetal.us