

Super Stud U-Trim: available in both 1/2" and 5/8" Depths



Super Stud metal U-Trim is used at the termination of a gypsum board finished wall or ceiling. This may be at a door or window opening, at a transition to a different type of finish, or at any edge where a clean, straight, smooth edge is required. The knurled leg of our U-Trim has a smooth, dull finish, specifically treated and perforated for optimal acceptance of gypsum- or chemical-based joint compounds: with maxi-

mum adhesion and minimal sag. U-Trim may be nailed, stapled, or screwed to the gypsum, wood, or steel substrate. Super Stud Trim products come in custom-fit cardboard packaging, to protect product edges from shipping damage. And, like all Super Stud steel products, U-Trim is Made in the USA, with zinc-coated steel: minimum 25% recycled content, and 100% recyclable.

Trim Depth	Trim Length	Quantity per carton	Cartons per skid	Knurled flange width
1/2"	10'-0" or 12'-0"	50	48	1.25"
5/8"	10'-0" or 12'-0"	50	48	1.25"

Available Thickness: 0.014"

Minimum Yield Strength: 33 KSI

Coating: G30 galvanized coating, in accordance with ASTM C645

Depth: 1/2" or 5/8" (see table above) Leg lengths: 1.25" and 1/2"

CODES & STANDARDS

Super Stud products comply with the applicable provisions of the following:

International Building Code (IBC) 2006 - 2018

Meets ASTM C754 when installed properly in structure

Sheet Steel: ASTM A1003 & ASTM A653

Zinc galvanized Coating: ASTM A653 & ASTM C645

Members & Tolerances: ASTM C645

3rd Party Certification:

Manufacturing verified & inspected by
Home Innovation Research Labs, Inc.