

PRODUCT SUBMITTAL SHEET

For more information or questions, please contact the technical department: technical@buysuperstud.com



1400T125-541 (50ksi) Track

Product Description: 14" Track 16GA (1-1/4" Leg, 54mil)


Coating: G60 (standard), G90 (special order)

Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES				
Web Depth	14 in.	Yield Strength, Fy	50 ksi	
Leg Width	1.25 in.	Design Thickness	0.0566 in.	
		Min. Steel Thickness	0.0538 in.	

*1 Web-height to thickness ratio exceeds 200. Web stiffeners are required at all support points and concentrated loads.

GROSS PROPERTIES			
Area (in2)	Total cross-sectional steel area	0.933	
Weight (lb/ft)	Linear weight per foot	3.17	
Ix (in ⁴)	Moment of inertia about the x-axis	19.987	
Sx (in³)	Section modulus about the x-axis	2.815	
Rx (in)	Radius of gyration about the x-axis	4.628	
ly (in⁴)	Moment of inertia about the y-axis	0.061	
Ry (in)	Radius of gyration about the y-axis	0.256	
EFFECTIVE PROPERTIES			
lx (in³)	Effective moment of inertia (x-axis)	16.406	
Sx (in³)	Effective section modulus (x-axis)	1.518	
Ma (in-k)	Allowable bending moment-effective section modulus	37.95	
Va _g (lb)	Allowable shear force in web	1160	
TORSIONAL PROPERTIES			
J x 1000 (in ⁴)	St. Venant torsional constant	0.9965	
Cw (in ⁶)	Warping constant	2.559	
Xo (in)	Distance from shear center to centroid	-0.299	
m (in)	Distance from shear center to mid-plane of web	0.209	
Ro (in)	Polar radius of gyration	4.645	
Beta	Torsional Flexural Constant	0.996	





CODES AND STANDARDS:

Super Stud products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M

Structural Members:

- ASTM C955; AISI S240
- Installed per ASTM C1007

Additional Standards:

• AISI S201; AISI S202

3rd Party Certification

For LEED Letter requests please submit through: www.buysuperstud.com