

400T125-30 Track


Product Description: 4" Track DW 20GA (1 1/4" Leg, 30mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 09.22.16 (Non-Structural Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	4 in.	Yield Strength, Fy	33 ksi
Flange Width	1.25 in.	Design Thickness	0.0312 in.
		Min. Steel Thickness	0.0296 in.

GROSS PROPERTIES		
Area (in ²)	Total cross-sectional steel area	0.203
Weight (lb/ft)	Linear weight per foot	0.69
I _x (in ⁴)	Moment of inertia about the x-axis	0.495
S _x (in ³)	Section modulus about the x-axis	0.239
R _x (in)	Radius of gyration about the x-axis	1.563
I _y (in ⁴)	Moment of inertia about the y-axis	0.028
R _y (in)	Radius of gyration about the y-axis	0.371
EFFECTIVE PROPERTIES		
I _x (in ³)	Effective moment of inertia (x-axis)	0.427
S _x (in ³)	Effective section modulus (x-axis)	0.177
M _a (in-k)	Allowable bending moment-effective section modulus	3.49
V _{a_g} (lb)	Allowable shear force in web	689
TORSIONAL PROPERTIES		
J x 1000 (in ⁴)	St. Venant torsional constant	0.0658
C _w (in ⁶)	Warping constant	0.085
X _o (in)	Distance from shear center to centroid	-0.632
m (in)	Distance from shear center to mid-plane of web	0.397
R _o (in)	Polar radius of gyration	1.726
Beta	Torsional Flexural Constant	0.866



CODES AND STANDARDS:

Super Stud products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M or equivalent
- Fire-Resistance (when applicable):
- UL Designs: U419, V438, V489, V498, W433, W440
- Fire Testing: ASTM E119; ANSI/UL 263
- **Nonstructural Members:**
- ASTM C645; AISI S220
- Installed per ASTM C754

Additional Standards:

- AISI S201; AISI S202

3rd Party Certification

For LEED Letter requests please submit through: www.buysuperstud.com