

600S125-30 (Standard Punch)



Product Description: 6" Stud DW 20GA (1 1/4" Leg, 30mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 09.22.16 (Non-Structural Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	6 in.	Yield Strength, F_y	33 ksi
Flange Width	1.25 in.	Design Thickness	0.0312 in.
Lip Length	0.188 in.	Min. Steel Thickness	0.0296 in.

GROSS PROPERTIES		
Area (in ²)	Total cross-sectional steel area	0.268
Weight (lb/ft)	Linear weight per foot	0.91
I_x (in ⁴)	Moment of inertia about the x-axis	1.276
S_x (in ³)	Section modulus about the x-axis	0.425
R_x (in)	Radius of gyration about the x-axis	2.182
I_y (in ⁴)	Moment of inertia about the y-axis	0.038
R_y (in)	Radius of gyration about the y-axis	0.376
EFFECTIVE PROPERTIES		
I_x (in ³)	Effective moment of inertia (x-axis)	1.222
S_x (in ³)	Effective section modulus (x-axis)	0.304
M_a (in-k)	Allowable bending moment-effective section modulus	6.00
M_{ad} (in-k)	Allowable bending moment-distortional buckling	4.91
V_a (lb)	Allowable shear force in web	468
$V_{a_{net}}$ (lb)	Allowable strong axis shear at punchout	468
TORSIONAL PROPERTIES		
$J \times 1000$ (in ⁴)	St. Venant torsional constant	0.087
C_w (in ⁶)	Warping constant	0.274
X_o (in)	Distance from shear center to centroid	-0.611
m (in)	Distance from shear center to mid-plane of web	0.401
R_o (in)	Polar radius of gyration	2.297
Beta	Torsional Flexural Constant	0.929



Non-structural punchout first punchout is centered 12" from beginning of member; subsequent punchouts are 24" on center (o.c.).
Center of last punchout is no less than 12" from end of member.

CODES AND STANDARDS:

Super Stud products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M or equivalent
- Fire-Resistance (when applicable):
- UL Designs: U419, V438, V489, V498, W433, W440
- Fire Testing: ASTM E119; ANSI/UL 263
- **Nonstructural Members:**
- ASTM C645; AISI S220
- Installed per ASTM C754

Additional Standards:

- AISI S201; AISI S202

3rd Party Certification

For LEED Letter requests please submit through: www.buysuperstud.com