

600T125-68 (50ksi) Track


Product Description: 6" Track 14GA (1-1/4" Leg, 68mil)

Coating: G60 (standard), G90 (special order)

Specification Section: 05.40.00 (Cold-Formed Metal Framing)

GEOMETRIC PROPERTIES			
Web Depth	6 in.	Yield Strength, F_y	50 ksi
Leg Width	1.25 in.	Design Thickness	0.0713 in.
		Min. Steel Thickness	0.0677 in.

GROSS PROPERTIES		
Area (in ²)	Total cross-sectional steel area	0.605
Weight (lb/ft)	Linear weight per foot	2.06
I_x (in ⁴)	Moment of inertia about the x-axis	2.970
S_x (in ³)	Section modulus about the x-axis	0.951
R_x (in)	Radius of gyration about the x-axis	2.216
I_y (in ⁴)	Moment of inertia about the y-axis	0.067
R_y (in)	Radius of gyration about the y-axis	0.332
EFFECTIVE PROPERTIES		
I_x (in ³)	Effective moment of inertia (x-axis)	2.936
S_x (in ³)	Effective section modulus (x-axis)	0.860
M_a (in-k)	Allowable bending moment-effective section modulus	25.74
V_a (lb)	Allowable shear force in web	5352
TORSIONAL PROPERTIES		
$J \times 1000$ (in ⁴)	St. Venant torsional constant	1.0251
C_w (in ⁶)	Warping constant	0.483
X_o (in)	Distance from shear center to centroid	-0.503
m (in)	Distance from shear center to mid-plane of web	0.329
R_o (in)	Polar radius of gyration	2.296
Beta	Torsional Flexural Constant	0.952



CODES AND STANDARDS:

Super Stud products comply with the applicable provisions of the following:

- International Building Code (IBC): 2006–2024
- AISI S100-16 (2020) w/S2-20
- Sheet Steel: ASTM A1003/A1003M; ASTM A653/A653M
- Galvanized Coating: ASTM A653/A653M

Structural Members:

- ASTM C955; AISI S240
- Installed per ASTM C1007

Additional Standards:

- AISI S201; AISI S202

3rd Party Certification

For LEED Letter requests please submit through: www.buysuperstud.com